

Hydrogen Generation From Electrolysis

Stephen Porter

Hydrogen Technology Group

Proton Energy Systems

May 23, 2005



PDP41

This Presentation Does Not Contain Any Proprietary or Confidential Information

Overview

Timeline

- ◆ Start Date March 2004
- ◆ End Date September 2007
- ◆ 10% Complete

Barriers

- ◆ Q. Cost
- ◆ R. System Efficiency
- ◆ S. Grid Electricity Emissions
- ◆ T. Renewable Integration

Budget

- ◆ Total Project \$3.8 million
 - 50% Cost Share
- ◆ \$245K Funding in FY04
- ◆ Limited FY05 Funding

Partners

- ◆ Air Products and Chemicals Inc.
- ◆ University of California, Irvine

Objectives

Develop an Efficient, Low-cost, Electrolysis Based Generation System Capable of Delivering 5000 psi Hydrogen to a Vehicle

- ◆ Determine Pathway to Optimum Electrolysis Based H2 Fueling
- ◆ Improve Subsystem / Component Performance, Cost, Durability
- ◆ Emphasis on Efficiency, Low-cost, and High Pressure
- ◆ Incorporate Renewable Wind Generated Power



Approach

Establish Fueling System Requirements

- ◆ Determine Daily Production / Storage Requirements for System
- ◆ Determine Applicable Codes and Standards, Present and Future
- ◆ Verify Range of Vehicle Fueling Requirements Including Pressure

Perform Conceptual Systems Design and Analyses

- ◆ Generate System Cost Vs. Performance Analysis Model
- ◆ Develop Conceptual System Design
- ◆ Perform Design Trades for Subsystems and Components

Perform Development Test on Key Subsystems / Components

- ◆ Prototype and Test to Substantiate Analytically Predicted Performance
- ◆ Development Tests of Low Cost Materials and Assembly Techniques

Accomplishments / System Analysis

Completed System Model Structure

- ◆ Output Directly Maps to the RD&D Technical Targets
- ◆ Compare System Benefits of New Concepts for Subsystems
- ◆ Two Discrete Station Sizes, 2 Kg/day and 100 Kg/day
- ◆ Basis of Cost Is 100 Units Produced Annually

Completed First Pass of Subsystem Models

- ◆ Basic Features Incorporated, Ready for Integration

Accomplishments / Cell Stack Cost Reduction

Completed Milestone On Schedule

Four Cost Reduction / Efficiency Opportunities Examined

- ◆ Efficiency Gains Through High Temperature Operation
- ◆ Optimization of Catalyst Loading for Performance and Cost
- ◆ Evaluation of Lower Cost / Higher Performance Catalyst
- ◆ Evaluation of Lower Cost / Higher Performance Ion Exchange Membranes

Changes Evaluated Have Potential of

- ◆ 7% Gain in Cell Stack Efficiency
- ◆ 30% Cost Reduction of MEA
- ◆ 8 to 10% Cost Reduction of Cell Stack


Combination of Opportunities Require Test

Accomplishments / Cell Stack Cost Reduction

Efficiency Gains Through High Temperature Operation

Demonstrated Higher Efficiency at Elevated Temperature

7% Gain in Efficiency Realized by Higher Operating Temperature



Accomplishments / Cell Stack Cost Reduction



Optimization of Catalyst Loading for Performance and Cost

Two Reduced Catalyst Scenarios Tested

- ◆ 33% Anode, 25% Cathode
- ◆ 66% Anode, 50% Cathode

Confirmed Rational for Long Term Testing to Determine True Performance

30% Cost Reduction in Catalyst With Equal Performance



Accomplishments / Cell Stack Cost Reduction

Evaluation of Lower Cost / Higher Performance Catalyst

Evaluated Five Alternate Cathode Electrode Catalysts


- ◆ Physical Characterization
- ◆ Electrode Fabrication
- ◆ MEA Fabrication
- ◆ Electrochemical Performance

Cell Voltage Efficiency Gains

Catalyst Cost Saving of 30%

Catalyst Synthesis
Processing Ease Resulted in
50% Labor Reduction

Approximately 10 Fold
Process Throughput
Improvement



Accomplishments / Cell Stack Cost Reduction

Lower Cost / Higher Performance Ion Exchange Membranes

Thinner Membranes (30%)


Evaluated

- MEA Manufacturability
- Cross-MEA Resistance
- Electrochemical Performance
- Chemical Stability / Durability

**Handling of Thinner
Membrane More Delicate**

**30% Cost Savings on
Membrane Material Possible**

**Long Term Durability Needs
to be Evaluated**



Accomplishments / Electrochemical Compressor

**Electrochemical Compressor
Feasibility Study Completed**

**Tests Performed on Single Cell
Electrolyzer Hardware**

**Ambient to 2,400 psi
Compression**


**Parameters Affecting
Performance Identified**

**Preliminary Study results
Encouraging**

- ◆ Throughput
- ◆ Efficiency

Merits Further Study

- ◆ Optimization of Cell Stack for
Compression




Accomplishments / Electrochemical Compressor

The Effect of Humidification on Electrochemical Compression Cell

Examined the Competing Effects of Maintaining Cell Hydration and Over Humidification

Stable Performance at 60% to 100% RH (60°C)




Accomplishments / Electrochemical Compressor

Polarization of the Electrochemical Compression Cell

**Cell Voltage Increased
With Pressure As
Expected**

**Increment Was
Proportionally Larger at
Higher Current Density**

- ◆ Larger Than Those Predicted by the Nernst Potentials
- ◆ Contact Resistance Increase Due to Internal Changes in Pressure




Accomplishments / Electrochemical Compressor

Compressed Hydrogen Throughput Capacity

Evaluated Compression
Throughput Vs. Output
Pressure From 250 psi
to 2,400 psi

High Throughput
Obtained With Usable
Current Densities

Increased Permeation at
Higher Pressures But
Proportionally Less of
an Overall Effect at
Higher Current Densities




Accomplishments / Electrochemical Compressor

Energy Consumption by Hydrogen Electrochemical Compression

Energy Consumption
Vs. Current Density
Evaluated

At Current Density of
720 mA/cm² ECC
Comparable to a
Measured Single
Stage Diaphragm
Compressor



Reviewer's Comments From 2004

Would Benefit From DFM Analysis of the Entire System in Addition to the Planned Volume Manufacture Analysis

Agree With Clarification

- ◆ System Analysis Captures Effect of Subsystem Technology Changes on Adjoining Subsystems and the Overall Conceptual System
- ◆ Design for Manufacturing Analysis Would Be Performed As Part of the Detailed Design of the Selected Subsystems In Combination

Future Work

Remainder of FY 2005

Station Design and Analysis

- ◆ Complete Fueling Station Analysis Model
- ◆ Complete Fueling Station Requirements
- ◆ Complete Conceptual Designs for 100 and 2 kg/day Stations

Cost Reduction Activity

- ◆ Renewable Interface / Power Conversion Study
- ◆ Dispensing System Cost Reduction Study
- ◆ Integrated System Cost Reduction Opportunity Study

FY 2006

- ◆ Scale Up of Promising Subsystems / Components
- ◆ 100kg/day System Size
- ◆ Prototype Testing

Publications and Presentations

None

Hydrogen Safety

The most significant hydrogen hazard associated with this project is:

This phase of the project is being conducted under laboratory conditions. The most significant hydrogen hazard is that typically associated with the laboratory use of high-pressure hydrogen. The hazard is a release of hydrogen due to loss of containment. This presents two hazards of about equal severity. First is the potential for injury due to exposure to a high-pressure (2,400 psig) gas stream or debris. Second, is the potential for fire upon release of hydrogen creating a combustible atmosphere.

Hydrogen Safety

Our approach to deal with this hazard is:

The hydrogen overpressure and release hazard for the test stand is mitigated in three ways. First, the system is proof pressure tested for leaks. Second, relief valves that are appropriately sized are placed at locations where there is a potential for over pressurization. Third, is the use of impact shields around the high-pressure portions of the system under test. In addition, the area where the test stations are located is monitored for proper ventilation, flame detection, and combustible gas detection. The monitoring system is hardwired into the main power feed and shuts down all test stations if there is an event.